



NOTES:

1. WEAKENED PLANE JOINTS SHALL BE INSTALLED AT BOTH SIDES OF A DRIVEWAY AND AT 10' INTERVALS OR MATCH ADJACENT CONSTRUCTION.
2. PORTLAND CONCRETE CEMENT MIX SHALL BE PER GREENBOOK (SSPWC), 520-C-2500.
3. REFER TO AMERICANS WITH DISABILITIES ACCESS REQUIREMENTS FOR DETAILS ON MAXIMUM PERMITTED SLOPES.
4. DRIVEWAY HIGHPOINT SHALL BE 3.5 INCHES, MINIMUM ABOVE STREET CENTERLINE.
5. COMPACTION OF NATIVE SUBGRADE SHALL MEET 95%.
6. STANDARD DOES NOT APPLY TO PROPERTIES WITHOUT ADJACENT OR CONTINUOUS CURB AND GUTTER OR SIDEWALK IMPROVEMENTS.
7. TO MINIMIZE SCRAPING $Y\% + Z\%$ SHALL BE LESS THAN 15%.
8. REFER TO STD. 109 FOR DECORATIVE DRIVEWAY APPROACHES.

CURB FACE	X
6"	3'
8"	4'



CITY OF LAGUNA BEACH PUBLIC WORKS DEPARTMENT

REV.	DATE

DRIVEWAY APPROACH I (FLARED)

APPROVED BY:

03/29/2022

MARK A. TRESTIK, CITY ENGINEER, R.C.E. 53708

DATE

STANDARD PLAN

102

1 OF 1