



PLAN

NOTES:

1. WEAKENED PLANE JOINTS SHALL BE INSTALLED AT BOTH SIDES OF A DRIVEWAY AND AT 10' INTERVALS OR MATCH ADJACENT CONSTRUCTION.
2. PORTLAND CONCRETE CEMENT MIX SHALL BE PER GREENBOOK (SSPWC), 520-C-2500.
3. REFER TO AMERICANS WITH DISABILITIES ACCESS REQUIREMENTS FOR DETAILS ON MAXIMUM PERMITTED SLOPES.
4. DRIVEWAY HIGHPOINT SHALL BE 3.5 INCHES, MINIMUM ABOVE STREET CENTERLINE.
5. COMPACTION OF NATIVE SUBGRADE SHALL MEET 95%.
6. TO MINIMIZE SCRAPING Y% + Z% SHALL BE LESS THAN 15%.

CURB FACE	X
6"	3'
8"	4'



CITY OF LAGUNA BEACH PUBLIC WORKS DEPARTMENT

REV.	DATE	DRIVEWAY APPROACH II (FLARED)	STANDARD PLAN 103
APPROVED BY: <i>Mark A. Trestik</i>		03/29/2022	1 OF 1
MARK A. TRESTIK, CITY ENGINEER, R.C.E. 53708		DATE	