



NOTES:

1. WEAKENED PLANE JOINTS SHALL BE INSTALLED AT BOTH SIDES OF A DRIVEWAY AND AT 10' INTERVALS OR MATCH ADJACENT CONSTRUCTION.
2. PORTLAND CONCRETE CEMENT MIX SHALL BE PER GREENBOOK (SSPWC), 520-C-2500.
3. REFER TO AMERICANS WITH DISABILITIES ACCESS REQUIREMENTS FOR DETAILS ON MAXIMUM PERMITTED SLOPES.
4. DRIVEWAY HIGHPOINT SHALL BE 3.5 INCHES, MINIMUM ABOVE FLOWLINE.
5. CURB SHALL BE INTEGRAL AND MATCH ADJACENT CONSTRUCTION.
6. 'R' EQUALS PARKWAY WIDTH, BUT SHALL BE A MINIMUM OF 3 FEET.
7. COMPACTION OF NATIVE SUBGRADE SHALL MEET 95%.
8. TO MINIMIZE SCRAPING Y% + Z% SHALL BE LESS THAN 15%.



CITY OF LAGUNA BEACH PUBLIC WORKS DEPARTMENT		DRIVEWAY APPROACH (RADIUS)		STANDARD PLAN 104
REV.	DATE	APPROVED BY: <i>Mark A. Trestik</i>	03/29/2022	1 OF 1
		MARK A. TRESTIK, CITY ENGINEER, R.C.E. 53708	DATE	