



- NOTES:**
1. ASPHALT SHALL BE TYPE C2-PG 64-10 (1/2"), OR AS DIRECTED BY THE ENGINEER.
 2. ASPHALT SHALL BE PLACED IN TWO INCH (2") LIFTS.
 3. EDGE OF SPEED HUMPS SHALL BE FIVE FEET (5') MINIMUM FROM EDGE OF DRIVEWAY.
 4. WHEREVER POSSIBLE SPEED HUMPS SHALL BE PLACED AT PROPERTY LINES.
 5. WARNING SIGNS W8-1 AND W13-1P, PER CA MUTCD (2014), SHALL BE INSTALLED IN EACH DIRECTION, AS DIRECTED BY THE ENGINEER.
 6. ADVANCED WARNING SIGN W84 (CA), PER CA MUTCD (2014), SHALL BE INSTALLED IN EACH DIRECTION, AS DIRECTED BY THE ENGINEER.



CITY OF LAGUNA BEACH PUBLIC WORKS DEPARTMENT		
REV.	DATE	APPROVED BY: <i>Mark A. Trestik</i>
		03/29/2022
MARK A. TRESTIK, CITY ENGINEER, R.C.E. 53708		DATE
		STANDARD PLAN
		115
		1 OF 1